

CIERA Industries Inc. 27902 Brookhaven Pl Valencia CA 91354 Ph: 661 263 8505

Fax: 661 263 8305

Picture	Part #	Description
2.8	BMSWM	Bracket Motor Short Wall Mount
		Motor Bracket for LT50 Star Head Motors
		Zinc plated steel
		Maximum weight capacity - 40LB
		Max Roll Ø 4 1/8"
		Stainless steel screws
		Bracket Motor Short Ceiling Mount
		Motor Bracket for LT50 Star Head Motors
3.8	DAACCAA	Zinc plated steel
	BMSCM	Maximum weight capacity - 40LB
		Max Roll Ø 4 1/8"
2.8		Stainless steel screws
		Bracket Idler Short
	BIS	Idler Bracket for LT50 Star Head Motors
3.8		Zinc plated steel and Delrin
		Stainless steel screws
		Maximum weight capacity - 40LB
2.8		Max Roll Ø 4 1/8"
<u> </u>		
3.7		Collapsible idler 2 inch
		Works with notched 2 inch tube and tubes with internal key
	CI2I	Black Composite Housing
		Maximum weight capacity - 40LB
<u>\$\phi_{2.0}\$</u>		Zinc plated steel Shaft
		Coupling Bracket Assy Short
2.8	CBAS	Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel
		Black Composite Housing
		Maximum weight capacity - 40LB
0.875		Max Roll Ø 4 1/8"

3.8		Bracket R24 Short
		Works with R24 Clutch
	DD246	Zinc plated steel
	BR24S	Max Roll Ø 4 1/8"
		Maximum weight capacity - 40LB
		Bracket Motor Long Ceiling Mount
		Motor Bracket for LT50 Star Head Motors
5.0	BMLCM	Zinc plated steel
	DIVILCIVI	Stainless steel screws
		Maximum weight capacity - 40LB
2.8		Max Roll Ø6 3/4"
		Bracket Motor Long Wall Mount
		Motor Bracket for LT50 Star Head Motors
2.8	BMLWM	Zinc plated steel
	DIVILANIAI	Stainless steel screws
3.6		Maximum weight capacity - 40LB
5.0		Max Roll Ø6 3/4"
		Bracket Idler Long
3.6		Idler Bracket for LT50 Star Head Motors
5.0	BIL	Zinc plated steel and Delrin
		Stainless steel screws
		Maximum weight capacity - 40LB
2.8		Max Roll Ø 6 3/4"
2.8		Counting Procket Assulance
3.6		Coupling Bracket Assy Long
3.6		Works with notched 2 inch tube and tubes with internal key
3.6	CBAL	
3.6	CBAL	Works with notched 2 inch tube and tubes with internal key
	CBAL	Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket
0.875	CBAL	Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket Delrin and Nylon Composit Components
	CBAL	Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket Delrin and Nylon Composit Components Maximum weight capacity - 40LB
0.875	CBAL	Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket Delrin and Nylon Composit Components Maximum weight capacity - 40LB Max Roll Ø 6 3/4"
0.875	CBAL	Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket Delrin and Nylon Composit Components Maximum weight capacity - 40LB Max Roll Ø 6 3/4" Motor Box Bracket Assembly
0.875		Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket Delrin and Nylon Composit Components Maximum weight capacity - 40LB Max Roll Ø 6 3/4" Motor Box Bracket Assembly Motor Bracket for LT50 Star Head Motors Powder coated 4 inch steel box bracket Stainless steel screws
0.875		Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket Delrin and Nylon Composit Components Maximum weight capacity - 40LB Max Roll Ø 6 3/4" Motor Box Bracket Assembly Motor Bracket for LT50 Star Head Motors Powder coated 4 inch steel box bracket

4.0	СВВА	Idler Box Bracket Assembly
		Idler Bracket for LT50 Star Head Motors
		Powder coated 4 inch steel box bracket
		Stainless steel screws and Delrin nest
		Maximum weight capacity - 40LB
		Max Roll Ø 3 3/4"
4.0		Coupling Box Bracket Assy
.875		Works with notched 2 inch tube and tubes with internal key
		Powder coated 4 inch steel box bracket
		Delrin and Nylon Composit Components
4.0		Maximum weight capacity - 40LB
		Max Roll Ø 3 3/4"
		Adjustable Coupling Bracket Assy Short Wall Mount
3.8		Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
	ACBAS-WM	Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
***		Max Roll Ø 3 7/8"
N. 8		Adjustable Coupling Bracket Assy Short Ceiling Mount
	ACBAS-CM	Works with notched 2 inch tube and tubes with internal key
12. A		Zinc plated steel bracket
		Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 3 7/8"
0.4		Adjustable Coupling Box Bracket Assy
	АСВВА	Works with notched 2 inch tube and tubes with internal key
		Powder coated 4 inch steel box bracket
		Delrin and Nylon Composit Components
0.4		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 3 3/4"
8.	ACBAL-CM	Adjustable Coupling Bracket Assy Long - Ceiling Mount
		Works with notched 2 inch tube and tubes with internal key
3.63		Zinc plated steel bracket
		Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 6 3/4"

3.63		Adjustable Coupling Bracket Assy Long - Wall Mount
		Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
	ACBAL-WM	Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 6 3/4"
2.82		Adjustable Idler Bracket Assy Short Ceiling Mount
-0-		Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
2.38	AIBAS-CM	Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 4 1/8"
2.38		Adjustable Idler Bracket Assy Short Wall Mount
		Works with notched 2 inch tube and tubes with internal key
6		Zinc plated steel bracket
7.82	AIBAS-WM	Delrin and Nylon Composit Components
2		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 4 1/8"
4.00	AIBBA	Adjustable Idler Box Bracket Assy
0		Works with notched 2 inch tube and tubes with internal key
		Powder coated 4 inch steel box bracket
		Delrin and Nylon Composit Components
4.00		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 3 3/4"
		Adjustable Idler Bracket Assy Long Ceiling Mount
5.5	AIBAL-CM	Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
93		Delrin and Nylon Composit Components
e,		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 6 3/4"
3.63	AIBAL-WM	Adjustable Idler Bracket Assy Long Wall Mount
M)		Works with notched 2 inch tube and tubes with internal key
2 6 0		Zinc plated steel bracket
2.82		Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 6 3/4"

4.97		Double Shade Motor Bracket
4.00		Works with LT50 Star Head Motors
		Zinc plated steel bracket
	DSMB	Zinc plated steel motor pins
	SSIVIE	Stainless steel screws
		Maximum weight capacity - 40LB
		Max Roll Ø 4" for each roll
4.97		Double Shade Idler Bracket
4.00		Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
	DSIB	Black Delrin Idler Nests
24.00		Stainless steel screws
		Maximum weight capacity - 40LB
		Max Roll Ø 4" for each roll
		Double Shade Coupler Bracket Assembly
		Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
	DSCBA	Delrin and Nylon Composit Components
		Bronze bushing
		Maximum weight capacity - 40LB
		Max Roll Ø 4" for each roll
		Double Shade Adjustable Coupler Bracket Assembly
		Works with notched 2 inch tube and tubes with internal key
		Zinc plated steel bracket
	DSACBA	Delrin and Nylon Composit Components
		1/2" height adjustability
		Maximum weight capacity - 40LB
		Max Roll Ø 4" for each roll
8:00		Double Shade Adjustable Idler Bracket
		Works with notched 2 inch tube and tubes with internal key
		Works with notched 2 inch tube and tubes with internal key Zinc plated steel bracket
	DSAIB	·
	DSAIB	Zinc plated steel bracket
	DSAIB	Zinc plated steel bracket Delrin and Nylon Composit Components
	DSAIB	Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability
	DSAIB	Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability Maximum weight capacity - 40LB
2.83	DSAIB	Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability Maximum weight capacity - 40LB Max Roll Ø 4" for each roll
2.83	DSAIB	Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability Maximum weight capacity - 40LB Max Roll Ø 4" for each roll Corner Coupler Assembly
2.83	DSAIB	Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability Maximum weight capacity - 40LB Max Roll Ø 4" for each roll Corner Coupler Assembly Works with notched 2 inch tube and tubes with internal key
2.83		Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability Maximum weight capacity - 40LB Max Roll Ø 4" for each roll Corner Coupler Assembly Works with notched 2 inch tube and tubes with internal key Zinc plated steel shaft and bracket
2.83		Zinc plated steel bracket Delrin and Nylon Composit Components 1/2" height adjustability Maximum weight capacity - 40LB Max Roll Ø 4" for each roll Corner Coupler Assembly Works with notched 2 inch tube and tubes with internal key Zinc plated steel shaft and bracket Black Nylon Housing

